Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/US05/005915

International filing date: 23 February 2005 (23.02.2005)

Document type: Certified copy of priority document

Document details: Country/Office: US

Number: 60/546,876


Filing date: 23 February 2004 (23.02.2004)

Date of receipt at the International Bureau: 23 March 2005 (23.03.2005)

Remark: Priority document submitted or transmitted to the International Bureau in

compliance with Rule 17.1(a) or (b)





'4(0) AND THO WINDOW THRESE, PRESENTS; SHAME (CONES;

UNITED STATES DEPARTMENT OF COMMERCE

United States Patent and Trademark Office

March 10, 2005

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE.

APPLICATION NUMBER: 60/546,876 FILING DATE: February 23, 2004

RELATED PCT APPLICATION NUMBER: PCT/US05/05915

Certified by

Under Secretary of Commerce for Intellectual Property and Director of the United States Patent and Trademark Office

PTO/SB/16 (5-03)
Approved for use through 04/30/2003. OMB 0651-0032
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

PROVISIONAL APPLICATION FOR PATENT COVER SHEET

This is a request for filing a PROVISIONAL APPLICATION FOR PATENT under 37 CFR 1.53(c).

INVENTOR(S)								
Chara Name (Fred and addition)				Residence				
Given Name (first and middle [if any]) Curtis		Family Name or Surname Clarke			(City and either State or Foreign Country) Grand Blanc, Michigan			4
Axel		Castronovas		San Antonio, Tex			P. 6	
James		Gavin		San Antonio, Tex			⁻ 8	Ш
Steven		Moon		Schwartz Creek,		ı	သည် လူထွ	
Additional inventors are being named on the separately numbered sheets attached hereto							54	nama k
TITLE OF THE INVENTION (280 characters max)							000	
EDGE CONTROLLED AIRBAG FOLD AND METHOD							1	THE
Direct all correspondence to: CORRESPONDENCE ADDRESS								_
Customer Number ————————————————————————————————————				ace Customer Number				
O.B	tomer Number here			Ва	Bar Code Label here			
Firm or Individual Name	1	e C. Begin	<u> </u>				-	
Address	Dinnin & Dunn, P.C.							
Address	Address 2701 Cambridge Ct. Suite 500							
City	Auburn	Hills	State	Michigan	ZIP	48326		
Country	USA		Telephone	(248) 364-2100	Fax	(248) 364-2200		
ENCLOSED APPLICATION PARTS (check all that apply)								
Specification Number of Pages 3 CD(s), Number								
Drawing(s) Number of Sheets Other (specify)								٦
Application Data Sheet. See 37 CFR 1.76							┚	
METHOD OF PAYMENT OF FIL	ING FEE	S FOR THIS PRO	VISIONAL A	PPLICATION FOR F	ATENT (check one)		
FILING FEE								
A check or money order is enclosed to cover the filing fees AMOUNT (\$)								
The Director is hereby authorized to charge filing								
fees or credit any overpayment to Deposit Account Number \$160.00								
Payment by credit card. Form PTO-2038 is attached.								
The invention was made by an agency of the United States Government or under a contract with an agency of the <u>Un</u> ited States Government.								
No.								
Yes, the name of the U.S. Government agency and the Government contract number are:								
Respectfully submitted,		1	_	Date	2/23/04			
SIGNATURE Lauremet Lym			_	REGISTRATION NO. 42,310				
TYPED or PRINTED NAME Laurence C. Begin			(if appr	(if appropriate) Docket Number: 5703-0006		,		
TELEPHONE(248) 364-2100				Docket	Desire Harrison.			

USE ONLY FOR FILING A PROVISIONAL APPLICATION FOR PATENT

This collection of information is required by 37 CFR 1.51. The information is used by the public to file (and by the PTO to process) a provisional application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 8 hours to complete, including gathering, preparing, and submitting the complete provisional application to the PTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Mail Stop Provisional Application, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

PROVISIONAL APPLICATION COVER SHEET Additional Page

PTO/SB/16 (8-00)

Approved for use through 10/31/2002. OMB 0651-0032
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a c ollection of information unless it displays a valid OMB control number.

Type a plus sign (+) **Docket Number** 5703-00062 inside this box INVENTOR(S)/APPLICANT(S) Residence Given Name (first and middle [if any]) Family or Surname (City and either State or Foreign Country) Paul Walsh Sylvan Lake, Michigan Humberto Hernandez Monclova Coahuala, Mexico Andres Rojero Monclova Coahuala, Mexico

Number _ 1 _ of _ 2 _

WARNING: Information on this form may become public. Credit card information should not be included on this form. Provide credit card information and authorization on PTO-2038.

CERTIFICATE OF I	MAIL" (37 CFR 1.10)	Docket No. 5703-00062						
Serial No.	Filing Date 2/23/04	Examiner	Group Art Unit					
Invention: EDGE CONTROLLED AIRBAG FOLD AND METHOD								
I hereby certify that the	e following correspondence:							
Provisional Application	ı (3 pages); Drawings (6 sheets);	Check No. 18786 for \$160.00; Postc	ard					
(Identify type of correspondence)								
		ce "Express Mail Post Office to Add for Patents, P.O. Box 1450, Alexa						
		Cathorino A. Saw						
		Catherine A. Sauve Glyped or Printed Name of Person-Mailing Correspondence)						
4 ,	(Vort Som	. 1					
		(Signature of Person Mailing Corn	espondence)					
•		EV 409387852 US						
		("Express Mail" Mailing Label Number)						
		·						
Note: Each paper must have its own certificate of mailing.								
		,						
•								

EDGE CONTROLLED AIRBAG FOLD AND METHOD DETAILED DESCRIPTION

Referring to Figure 1, there is shown an airbag folding apparatus 10 in accordance with a preferred constructed embodiment of the present invention. Apparatus 10 preferably includes a platen 12 and a plurality of folding blocks 14a-b and 16a-b. In a preferred embodiment, apparatus 10 is operated by placing an airbag such as a substantially circular airbag 20 on platen 12 and folding it by drawing blocks 14a-b and 16a-b inwardly, compressing airbag 20 between the blocks and forming the same into a relatively compact shape for positioning in an airbag housing (not shown). Referring also to Figure 2, there is shown airbag 20 partially compressed/folded between blocks 14a and 14b. It should be appreciated that although a circular airbag is shown other airbag designs may be useful with the present invention. All the component parts of the present invention may be manufactured from known materials and by known processes.

In a preferred embodiment, each of blocks 14a and 14b are equipped with slidable blades or retaining tabs 22a and 22b that assist in holding airbag 20 against platen 12 during a folding operation. As blocks 14a-b and 16a-b are drawn inwardly, for example with a pneumatic or hydraulic actuator retaining tabs 22a and 22b preferably prevent or minimize the tendency for airbag 20 to bunch upwardly away from platen 12. This retention prevents airbag 20 from folding inwardly such that a periphery of the airbag is captured within the folds. An upper retaining plate 30, illustrated in Figure 2 may be employed to enhance compression of airbag 20 by providing for a downward force against the compressing airbag.

A variety of constructions and features are contemplated for retaining tabs 22a and 22b. In one preferred embodiment, tabs 22a and 22b are reciprocable relative to their respective blocks 14a and 14b. Turning also to Figures 3a-b and 4a-b, there are shown blocks 14a and 14b with tabs 22a and 22b, respectively, slidably positioned therein. Each of tabs 22a and 22b are preferably equipped with an outer rail 24a-b and inner rail 26a-b (inner rail not illustrated in Figure 4(a)). The outer rails 24a-b are preferably positioned at an outer end of the tabs, and allow an operator or actuator to draw tabs 22a and 22b outwardly of blocks 14a and 14b. Upon compression/folding of airbag 20 to its desired state, rails 24a and 24b can be used to pull tabs 22a and 22b out of

engagement with airbag 20. In this manner, an airbag ejector (not shown) can be used to push the now folded airbag 20 up away from or off of platen 12, for positioning in a housing. Any of a variety of structural means can be used to ensure that tabs 22a and 22b are not pulled completely out of blocks 14a and 14b. For example, tabs 22a and 22b can be formed having a relatively small projection that engages with a complementary portion of the block and prevents complete disengagement therefrom. Inner rails 26a and 26b are preferably provided for positive positioning of tabs 22a and 22b when they are slid through blocks 14a and 14b and positioned above airbag 20. As illustrated in Figure 2, inner rails 26a and 26b are preferably positioned on tabs 22a and 22b such that they allow insertion of the tabs through the block only up to a desired point, or extent above airbag 20.

Although apparatus 10 is illustrated as having only two blocks (14a and 14b) equipped with tabs 22a and 22b, it should be appreciated that other embodiments are contemplated wherein all of the blocks or fewer of the blocks are provided with tabs. Moreover, all the tabs need not be reciprocable. Figure 8 illustrates an embodiment wherein a folding block 114 is equipped with a tab 122 rigidly affixed thereto. Figure 9 illustrates yet another embodiment wherein a set of folding blocks 116a, 116b and 116c is provided having angled engagement surfaces 119 and 121. In the Figure 9 embodiment, engagement surfaces 119 and 121 are positioned at an acute angle relative to the platen (not shown). Thus, during operation, the angled surfaces assist in preventing undesirable upward movement of the airbag during compression/folding.

Turning now to Figures 5-7, there are shown various views of a folding block 115 according to yet another embodiment of the present invention. Block 115 is preferably equipped with a retainer 222 that comprises an upwardly opening slot 223 adapted to receive an end of an airbag 220. Prior to a folding operation, the end of airbag 220 is placed in slot 223. As airbag 220 is compressed inwardly, the engagement of the end of airbag 220 in slot 223 prevents undesirable upward movement of a periphery of airbag 220 from a platen 212. Embodiments are contemplated wherein retainer 222 is made from a resilient material such that insertion of airbag 220 in channel 223 provides for a resilient clamping force on the airbag. Stated another way, retainer 222 may be formed from a springy or rubbery material such that when an edge of airbag 220 is

pushed into channel 223, it is retained therein. Figure 6a depicts an embodiment wherein a spring tab 222 is provided that clamps airbag 220 against block 215 with a spring force.

In a related embodiment, the present invention provides a method of folding or compressing an airbag. The method includes the step of placing an airbag 20 substantially flat upon a folding platen 12 between a plurality of blocks 14a-b and 16a-b, having means for retaining outer edges of the airbag 20. Next, the blocks are drawn inwardly about the airbag to effect a folding or compression thereof. When the airbag reaches the desired state, the edges are disengaged from the blocks, and an airbag ejector is actuated to push the folded airbag away from the platen and into an airbag housing.

The present invention offers numerous advantages over many known airbag folding designs. In particular, retention of the edge of the airbag during folding has been shown to reduce the likelihood of the perimeter of the airbag becoming trapped inside the folds, producing superior deployment characteristics in certain environments. Further, the overall consistency of the folding process in improved.

The present description is for illustrative purposes only, and should not be construed to narrow the breadth of the present invention in any way. Thus, those skilled in the art will appreciate that various modifications might be made to the presently disclosed embodiments without departing from the spirit and scope of the present invention.

This Page Is Inserted by IFW Operations and is not a part of the Official Record

BEST AVAILABLE IMAGES


Defective images within this document are accurate representations of the original documents submitted by the applicant.


Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problem Mailbox.








Figure 3(a)

